

Dräger X-am[®] 7000 Portable Multi Gas Detector

Dräger X-am 7000 is the solution for the simultaneous and continuous measurement of up to five gases. It is the ideal companion in a variety of applications where the reliable detection of oxygen, toxic and combustible gases and vapors are necessary.



ST-11846-2008

FLEXIBILITY THROUGH SENSOR VARIETY

The extensive portfolio of over 25 different DrägerSensors enables the detection of more than 100 gases and vapors. The Dräger X-am 7000 can be equipped with three electrochemical, and two catalytic bead, infrared or photo ionization sensors. During operation, it is also possible with the catalytic-Ex sensor to change the gas being measuring or the measurement range of the sensor. In this way, the instrument can be easily adapted to various applications. DrägerSensors are renowned for their fast response time, minor cross sensitivities, high level of accuracy and long lifetimes.

INTELLIGENT AND INTERCHANGEABLE SENSORS

In addition to the electrochemical sensors, the catalytic, infrared and photo ionization sensors are automatically recognized by the instrument upon insertion. All sensors are pre-calibrated, and therefore a reconfiguration of the Dräger X-am 7000 can be done by simply changing the sensor. No additional service or maintenance is necessary.

POISON RESISTANT EX-SENSOR

Advanced safety in explosive atmospheres: thanks to the high sensitivity of the innovative Ex-sensor to combustible organic

vapors the Dräger X-am 7000 warns reliable of danger of explosions. It not only responds quickly to combustible gases and vapours, it is also characterised by its high resistance against silicone and hydrogen sulphide contamination. In combination with the high degree of drift stability, this resistance enables an extraordinarily long service life of more than 4 years. This will reduce your operational costs.

ROBUST AND WATERTIGHT

A specially designed rubber boot protects the instrument against damage even from a drop of 1.5 m or 5 ft. In addition to the built in dust and water filter, the Dräger X-am 7000 can be submersed in up to 1 m or 3 ft. of water without damage.

BUILT FOR LONGEVITY

The completely new design of the rechargeable battery pack with intelligent charging-management guarantees full functionality of the instrument over a period of up to 20 hours. An alkaline battery pack is also available. The DrägerSensors used in the Dräger X-am 7000 have a typical lifetime of over 5 years. If a sensor exchange should become necessary, the modular approach of the instrument allows for this in a few simple steps.



ST-1465-2008

Dräger X-am 7000
Modular, rugged and water-tight complete with an integrated high-performance pump.

MULTIPLE ALARMS

Alarm conditions can not be ignored because of the extremely loud multi-tone horn. In addition, the visual alarm can be seen 360°, ensuring that the user notices the warning. By generating an optional life-signal every six seconds, the Dräger X-am 7000 confirms that it is functioning properly.

STRONG INTEGRATED PUMP

The built-in high-performance pump makes it possible to sample gas using a hose up to 45 m/150 ft. long. The operation of the pump is continuously monitored, and the instrument will generate an alarm if the flow of gas reduces.

EASY DETECTION OF LEAKAGES

A flexible "gooseneck" probe eases the search for leakages on pipelines, valves,

flanges, etc. In the tracking-mode, the instrument generates an increasing or decreasing rate of beeps, depending on the gas concentration detected.

INFORMATION AT ONE GLANCE

The large graphic display and the auto-zoom function during alarms guarantee an easy recognition of the measurement values and symbols displayed for immediate reaction to the situation or hazards. All information is provided in plain text for easy understanding.

INTUITIVE SOFTWARE FUNCTIONS

The software menu within the Dräger X-am 7000 was designed in partnership with our customers making it simple and easy to use. With the help of Dräger CC-Vision software, up to 5 different detection applications can

be saved within the instrument. By doing so, the use of different instrument configurations can be set for that specific application.

During operation, a simple change between these set parameters can be done via the instrument's menu.

DATA MANAGEMENT

An integrated data logger logs up to 3000 sets of values – that equals 100 hours when recording one set per minute. The data can then be transferred to and evaluated on a PC using an infrared interface together with the Dräger GasVision software package.

DrägerSensors

Space for up to 5 sensors, 3 electrochemical and 2 catalytic bead or infrared sensors or a photo ionization detector (PID).

Alarm functions

360° visible and > 100 dB multi-tone audible alarm.

Robust enclosure

Rugged, water-tight with a standard integrated rubber boot.

Large display

Clearly structured, scratch resistant display with information in plain text.



ST-67-2006

ORDER INFORMATION

Description

Dräger X-am 7000, basic unit including a calibration adapter, water- and dust-filter

• In order to receive a fully operational unit, a power pack and up to 5 sensors have to be ordered. An optional, integrated pump or data logger can also be included.

Order code

83 17 400

Power supply units

Rechargeable power pack NiMH 4.8 V / 3.0 Ah

83 17 408

Rechargeable power pack NiMH 4.8 V / 6.0 Ah

83 17 454

Alkaline power pack

83 17 550

Alkaline batteries (4 pcs.)

83 17 447

Charging accessories

Charging module

83 16 487

Power supply for up to eight charging modules

83 15 805

Power supply for one charging module

83 15 635

Power supply for up to two charging modules

83 16 994

Power supply for vehicles

83 12 645

Car mounting kit

83 18 169

ORDER INFORMATION

Description	Measuring range	Order code
Infrared Sensors		
DrägerSensor Smart IR Ex	0 – 100 %LEL 0 – 100 Vol.-% CH ₄	68 10 460
DrägerSensor Smart IR CO ₂	0 – 5 Vol.-%	68 10 590
DrägerSensor Smart IR CO ₂ HC	0 – 100 Vol.-%	68 10 599
Catalytic Bead Sensors		
DrägerSensor Smart CatEx PR	0 – 100 %LEL	68 12 970
DrägerSensor Smart CatEx HC PR	0 – 100 %LEL 0 – 100 Vol.-% CH ₄	68 12 980
DrägerSensor Smart CatEx FR PR	0 – 100 %LEL 0 – 100 Vol.-% CH ₄	68 12 975
PID Sensor		
DrägerSensor Smart PID	0 – 2000 ppm	83 19 100
Electrochemical Sensors		
DrägerSensor XS 2 CO	0 – 2000 ppm	68 10 365
DrägerSensor XS EC CO	0 – 2000 ppm	68 09 105
DrägerSensor XS R CO	0 – 2000 ppm	68 10 258
DrägerSensor XS EC CO HC	0 – 10 000 ppm	68 09 120
DrägerSensor XS 2 H ₂ S	0 – 100 ppm	68 10 370
DrägerSensor XS 2 H ₂ S SR	0 – 100 ppm	68 10 575
DrägerSensor XS EC H ₂ S 100	0 – 100 ppm	68 09 110
DrägerSensor XS EC H ₂ S HC	0 – 1000 ppm	68 09 180
DrägerSensor XS R H ₂ S	0 – 100 ppm	68 10 260
DrägerSensor XS 2 O ₂	0 – 25 Vol.-%	68 10 375
DrägerSensor XS EC O ₂ 100	0 – 100 Vol.-%	68 09 550
DrägerSensor XS EC O ₂ LS	0 – 25 Vol.-%	68 09 130
DrägerSensor XS R O ₂	0 – 25 Vol.-%	68 10 262
DrägerSensor XS EC Amine	0 – 100 ppm	68 09 545
DrägerSensor XS EC Cl ₂	0 – 20 ppm	68 09 165
DrägerSensor XS EC ClO ₂	0 – 20 ppm	68 11 360
DrägerSensor XS EC CO ₂	0 – 5 Vol.-%	68 09 175
DrägerSensor XS EC COCl ₂	0 – 10 ppm	68 08 582
DrägerSensor XS EC H ₂	0 – 2000 ppm	68 09 185
DrägerSensor XS EC H ₂ HC	0 – 4 Vol.-%	68 11 365
DrägerSensor XS EC HCN	0 – 50 ppm	68 09 150
DrägerSensor XS EC Hydride	0 – 20 ppm	68 09 135
DrägerSensor XS EC NH ₃	0 – 300 ppm	68 09 145
DrägerSensor XS EC NO	0 – 200 ppm	68 09 125
DrägerSensor XS EC NO ₂	0 – 50 ppm	68 09 155
DrägerSensor XS EC Odorant	0 – 40 ppm	68 09 200
DrägerSensor XS EC OV	0 – 200 ppm	68 09 115
DrägerSensor XS EC OV-A	0 – 100 ppm	68 09 522
DrägerSensor XS EC PH ₃ HC	0 – 1000 ppm	68 09 535
DrägerSensor XS EC SO ₂	0 – 100 ppm	68 09 160
Calibration and Communication Accessories		
Calibration adapter		83 17 656
Sensor extension cable for the calibration with vapors		83 17 970
Dräger X-am 7000 E-Cal Module		83 17 705
Dräger Bump Test Station for Dräger X-am 7000		83 19 072
Complete with one test gas cylinder 58 L (gas and concentration variable)		
Dräger Bump Test Station for Dräger X-am 7000, not including gas cylinder		83 18 909
Printer Set for Dräger Bump Test Station Dräger X-am 7000		83 21 009
Consisting of: Dräger Bump Test Station, Dräger Mobile Printer, single charger, rechargeable NiMH batteries, USB connection cable, positioning aid, Dräger CC-Vision (not including gas cylinder)		
Printer Set for Dräger Bump Test Station Dräger X-am 7000 (same contents as 83 21 009), Complete with one test gas cylinder 58L (gas and concentration variable)		83 21 020
Dräger GasVision		83 14 034
Dräger CC-Vision		Freeware



Dräger X-am 7000:
Leak search made easy through the generation of a tracking sound.



Dräger X-am 7000:
High-performance pump simplifies confined space entry.

TECHNICAL DATA

Dimensions (W x H x D)	150 x 140 x 75 mm; 5.9 x 5.6 x 3 in.	
Weight	Instrument	600 g; 21 oz.
	Rechargeable battery	490 g; 17 oz. (3.0 Ah) 730 g; 26 oz. (6.0 Ah)
Ambient conditions	Temperature	-20 to +55 °C, short-term -40 to +60 °C -5 to +105 °F, short-term -40 to +130 °F
	Pressure	700 to 1300 hPa
	Humidity	10 to 95 % r.h.
Ingress protection	IP 67	
Battery life	NiMH (4.8 V / 3.0 Ah)	> 9 hours
	NiMH (4.8 V / 6.0 Ah)	> 20 hours
	Alkaline	> 20 hours
Alarms	Visual 360° flashing LEDs, audible alarm (> 100 dB at 30 cm or 1 ft.)	
Charging time	3.5 to 7 hours, depending on battery type	
Pump mode	Maximum hose length of 45 m; 150 ft.	
Approvals	ATEX	II 2G Ex d ia IIC T4 Gb -20 ≤ Ta ≤ +60 °C (NiMH) -20 ≤ Ta ≤ +40 °C (Alkaline) I M2 Ex d ia I Mb BVS 03 ATEX E 371 X Measurement performance certificate according to: EN 50271:2001 EN 60079-29-1 (for the CatEx sensors from methane to nonane and infrared sensors) EN 45544-1 + 2 (CO, H ₂ S, CO ₂) EN 50101 (O ₂)
	MED	Marine Equipment Directive 96/98/EC
	UL	Class I, Div 1, Group A, B, C, D Temp. code T4 -20 ≤ Ta ≤ +60 °C (NiMH) -20 ≤ Ta ≤ +40 °C (Alkaline)
	CSA	Class I, Div 1, Group A, B, C, D Temp. code T4 -20 ≤ Ta ≤ +60 °C (NiMH) -20 ≤ Ta ≤ +40 °C (Alkaline)
	IECEX	Ex d ia IIC T4 Gb -20 ≤ Ta ≤ +60 °C (NiMH) -20 ≤ Ta ≤ +40 °C (Alkaline) Ex d ia I Mb
	CE-mark	Electromagnetic compatibility (directive 2004/108/EG)

CORPORATE HEADQUARTERS

Drägerwerk AG & Co. KGaA
Moislinger Allee 53–55
23558 Lübeck, Germany

www.draeger.com

P. R. CHINA

Dräger Safety Equipment
(China) Co., Ltd.
A22 Yu An Rd, B Area,
Tianzhu Airport Industrial Zone,
Shunyi District, Beijing 101300
Tel +86 10 80 49 80 00
Fax +86 10 80 49 80 05

FRANCE

Dräger Safety France SAS
3c route de la Fédération,
BP 80141
67025 Strasbourg Cedex 1
Tel +33 3 88 40 76 76
Fax +33 3 88 40 76 67

MEXICO

Dräger Safety S.A. de C.V.
Av. Peñuelas No. 5 Bodega No. 37
Fraccionamiento Industrial
San Pedrito
Querétaro, Qro México
Tel +52 442 246-1113
Fax +52 442 246-1114

NETHERLANDS

Dräger Safety Nederland B.V.
Edisonstraat 53
2700 AH Zoetermeer
Tel +31 79 344 46 66
Fax +31 79 344 47 90

REGION ASIA PACIFIC

Dräger Safety Asia Pte Ltd
67 Ayer Rajah Crescent
#06-03
Singapore 139950
Tel +65 68 72 92 88
Fax +65 65 12 19 08

REGION CENTRAL

AND SOUTH AMERICA
Dräger Panama S. de R.L.
Complejo Business Park,
V tower, 10th floor
Panama City
Tel +507 377-9100
Fax +507 377-9130
contactcsa@draeger.com

REGION MIDDLE EAST, AFRICA

Dräger Safety AG & Co. KGaA
Branch Office
P.O. Box 505108
Dubai, United Arab Emirates
Tel +971 4 4294 600
Fax +971 4 4294 699
contactuae@draeger.com

SPAIN

Dräger Safety Hispania S.A.
Calle Xaudaró 5
28034 Madrid
Tel +34 91 728 34 00
Fax +34 91 729 48 99

UNITED KINGDOM

Dräger Safety UK Ltd.
Blyth Riverside
Business Park
Blyth, Northumberland
NE24 4RG
Tel +44 1670 352-891
Fax +44 1670 356-266

USA

Dräger Safety, Inc.
101 Technology Drive
Pittsburgh, PA 15275
Tel +1 412 787 8383
Fax +1 412 787 2207

AUSTRALIA

Dräger Safety Pacific Pty. Ltd.
Axxess Corporate Park
Unit 99, 45 Gilby Road
Mt. Waverley Vic 3149
Tel +61 3 92 65 50 00
Fax +61 3 92 65 50 95

CANADA

Dräger Safety Canada Ltd.
7555 Danbro Crescent
Mississauga, Ontario L5N 6P9
Tel +1 905 821 8988
Fax +1 905 821 2565

Manufacturer:

Dräger Safety AG & Co. KGaA
Revalstraße 1
23560 Lübeck, Germany